

TOMORROW'S TECHNOLOGY TODAY




DHM-72X10/FS(BB)
 540~550W

[Full Screen] P V M o d u l e

No Dust and Dirt on the Surface Increase Power Generation

Quality Guarantee

- 12-year → Material & technology warranty
- 25-year → Linear power output warranty



- DAH Solar Linear power output guarantee
- Standard Linear power output guarantee

Comprehensive Products & System Certificates



IEC 61215 / IEC 61730 / CE / FIDE / INMETRO
 ISO 45001 : 2018/International standards for occupational health & safety
 ISO 14001 : 2015/Standards for environmental management system
 ISO 9001 : 2015/Quality management system



Increase power generation by 6.15%
 Panel is capable to decrease power generation loss caused by Dust, reduce the hot spot risk.



Curved Surface 128° R Angle
 Reduce holding pressure by 75%+
 Curved Frame with ergonomic Design, optimized Delivery and Installation Experience.



Revolutionary Assembling Technology
 Using excellent frame assembling technology,
 Strong Adhesion, Durable in Use.



Excellent mechanical load capacity
 Certified by Dust-Sand, Salt-Mist, Ammonia etc.
 weather resistance tests and enhanced mechanical load: wind load (2400 Pascal) and snow load (5400 Pascal).

DHM-72X10/FS(BB)

540~550W




Mechanical Specification

Cable	4.0mm ² , 300/400mm in length,
(Including connector)	length can be customized
No.of Cells	144 (6x24)
Glass	3.2mm High Transmission, Antireflection Coating
Junction box	IP68, 3 Bypass Diodes
Connector	MC4 Compatible
Weight	29kg
Cells Type	Mono 182x91mm
Dimension (LxWxT)	2279x1134x32mm
Packing	34pcs/pallet, 680pcs/40HQ

Operating Parameters

Maximum system voltage	1500V DC
Operating Temperature	-40 ~ +85°C
Maximum series fuse rating	25A
Snow load, frontside/Wind load, backside	5400Pa/2400Pa
Nominal operating cell temperature	45°C±2°C
Application level	Class A

Design



STC ———Electrical Characteristics

Module Type	DHM-72X10/FS(BB)		
Maximum Power (Pmax/W)	540	545	550
Open-circuit Voltage (Voc/V)	49.8	50.0	50.2
Maximum Power Voltage (Vmp/V)	42.0	42.2	42.4
Short-circuit Current (Isc/A)	13.66	13.72	13.78
Maximum Power Current (Imp/A)	12.86	12.91	12.97
Module Efficiency (%)	20.89	21.09	21.30

Power Tolerance: 0~+5W, Temperature Coefficient of Isc: 0.05%/°C, Temperature Coefficient of Voc: -0.31%/°C, Temperature Coefficient of Pmax: -0.35%/°C

Standard Test Environment : Irradiance 1000W/m², Cell temperature 25°C, Spectrum AM1.5

NOCT ———Electrical Characteristics

Maximum Power (Pmax/W)	402	405	409
Open-circuit Voltage (Voc/V)	46.7	46.9	47.1
Maximum Power Voltage (Vmp/V)	39.4	39.6	39.8
Short-circuit Current (Isc/A)	11.04	11.09	11.13
Maximum Power Current (Imp/A)	10.20	10.24	10.29

Standard Test Environment : Irradiance 800W/m², Ambient temperature 20°C, Spectrum AM1.5, Wind speed 1m/s

I-V Curve DHM-72X10/FS(BB)-550W

